

View Online at <https://aerobasegroup.com/nsn/4720-01-555-6973>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

28.4 degrees fahrenheit single response and 95.0 degrees fahrenheit single response

**Outside Diameter:**

1.060 inches

**Minimum Inside Bending Radius:**

3.100 inches

**End Application:**

Lio/tc piping

**Connection Style:**

Gasket seal / optional end 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel all ends

**Connection Type:**

Threaded internal boss 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

4400.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire err-100

**Maximum Operating Pressure:**

1100.0 pounds per square inch

**Thread Size:**

1.250 inches 1st end

**Hydrostatic Test Pressure:**

2200.0 pounds per square inch

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

29.750 inches working

**Product Name:**

Flex hose lcl-fh-32

**Special Features:**

Hose has internal support, nuts have lockwire holes, mates to cpv h849t-12

**Media For Which Designed:**

Refrigerant 13 single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0