NSN 4720-01-556-0474

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-556-0474

Cross Sectional Shape: Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.401 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds Connection Style:
Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.401 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.401 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
Thread Direction: Right-hand 1st end Inside Diameter: 0.401 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
Right-hand 1st end Inside Diameter: 0.401 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
Inside Diameter: 0.401 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
0.401 inches Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
Tempurature Rating: -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
Outside Diameter: 0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
0.615 inches Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
Minimum Inside Bending Radius: 2.875 inches End Application: Nha 6393516; used on asds
2.875 inches End Application: Nha 6393516; used on asds
End Application: Nha 6393516; used on asds
Nha 6393516; used on asds
Connection Style:
Gasket seal / optional end 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal boss 2nd end
Thready Qty Per Inch (tpi):
16 2nd end
Burst Test Pressure:
12000.0 pounds per square inch
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.812 inches 2nd end
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
11.750 inches working
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a

--

NSN 4720-01-556-0474

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0