Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-557-3081

Round Thread Direction: Right-hand all ends Inside Diameter: 0.375 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.765 inches Minimum Inside Bending Radius:	Cross Sectional Shape:	
Thread Direction: Right-hand all ends Right-hand all ends Inside Diameter: 0.375 inches Tempurature Rating: 40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Cutside Diameter: 0.765 inches Minimum Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Style: Straight all ends Connection Type: Thread enters to use all ends Enter Pressure: 1600.0 pounds per square inch single response 151 all ends Exter Pressure: 1600.0 pounds per square inch single response 151 algor braided fiber Maximum Operating Pressure: 1600.0 pounds per square inch single response 152 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber Maximum Operating Pressure: 1630.0 pounds per square inch single response 154 algor braided fiber 1550 inches all ends 1550 inches all ends 1550 inches working 1550 inches work	-	
Right-hand all ends Inside Diameter: 0.375 inches Tempurature Rating: 40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.765 inches Minimum Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Thready City Per Inch (tpi): 16 all ends Bury Test Pressure: 1600.0 pounds per square inch single response Layer Composition And Location: 18 layer braided fiber Muton Dynamic Pressure: 19 dos guares inch single response Thread Size: 0.688 inches all ends Horder Ley Per Sure: 19 dos guares inch single response Layer Composition And Location: 19 dos guares inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 0.688 inches all ends Hydrostatic Test Pressure: 19 dos guares inch single response Thread Size: 0.788 inches all ends Hydrostatic Test Pressure: 19 dos guares inch single response Inside Surface Condition: 19 dos guares inch single response Inside Surface Condition: 19 stories working		
niside Diameter: 0.375 inches Tempurature Rating: -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.765 inches Minimun Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 18 tayer braided fiber Maximu Operating Pressure: 000.0 pounds per square inch single response Chread Size: 0.688 inches all ends Hydrostatic Test Pressure: 0.688 inches working </td <td></td> <td></td>		
0.375 inches +0.0.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.755 inches Minimun Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Straight all ends End Connection Design: Straight all ends Connection Type: Thready Dyper Inch (tpi): 16 all ends Burst Test Pressure: 18000.0 pounds per square inch single response Layer Draided fiber Maximum Operating Pressure: 1900.0 pounds per square inch single response Layer Draided fiber Maximum Operating Pressure: 1000.0 pounds per square inch single response Layer Draided fiber Maximum Operating Pressure: 1088 inches all ends Hydroxattic Test Pressure: 0.808 inches all ends Hydroxattin Test Pressure: 0.808 inches all ends Hydroxattic Test Pressure: 0.808 inches all ends Hydroxattin Test		
Tempurature Rating: -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.765 inches Minimum Inside Bending Radius: 2.500 Inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Enterst Pressure: 16 all ends Burst Test Pressure: 16 000.0 pounds per square inch single response Layer Orngoition And Location: 1st layer braided fiber Maximum Operating Pressure: 000.0 pounds per square inch single response Ender Size: 0.88 Inches all ends Hydrostatic Test Pressure: 0.88 Inches all ends Hydrostatin Test pressure:		
-40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response Outside Diameter: 0.765 inches Minimum Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 18 tayer braided fiber Maximum Operating Pressure: 0.688 inches all ends Hydrostatic Test Pressure: 0.680 inches all ends Hydrostatic Test Pressure: Smooth Maseuring Method And Length: 1.5.00 inches working<	Tempurature Rating:	
Outside Diameter: 0.765 inches Minimum Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Threaded internal tube all ends Thready Gy Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 0.00.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 800.0 pounds per square inch single response Inside Surface Condition: Smooth Maseuring Method And Length: 1.3.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends		
2765 inches Minimum Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Threaded internal tube all ends Thready Oty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 000.0 pounds per square inch single response Thread Size: 0.888 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:		
Minimun Inside Bending Radius: 2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Oty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximun Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.888 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Thread Size: 0.888 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:		
2.500 inches Exterior Color: Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Oty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches: working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Minimum Inside Bending Radius:	
Black End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Oty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Midrostatic Test Pressure: 15 Jasson inches working Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	2.500 inches	
End Application: Midbody external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Oty Per Inch (tpi): 16 all ends Burst Test Pressure: 16 doll ends Burst Test Pressure: 16 000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Exterior Color:	
Mixed external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 0.600.0 pounds per square inch single response Inside Surface Condition: Sinooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends	Black	
Mixed external piping Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 0.600.0 pounds per square inch single response Inside Surface Condition: Sinooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends		
Connection Style: Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:		
Swivel nut, gasket seal all ends End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Messuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:		
End Connection Design: Straight all ends Connection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 0.00.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends	-	
Straight all ends Connection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	-	
Conection Type: Threaded internal tube all ends Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	-	
Thready Qty Per Inch (tpi): 16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends	-	
16 all ends Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Threaded internal tube all ends	
Burst Test Pressure: 16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Thready Qty Per Inch (tpi):	
16000.0 pounds per square inch single response Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	16 all ends	
Layer Composition And Location: 1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Mode Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Burst Test Pressure:	
1st layer braided fiber Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	16000.0 pounds per square inch single response	
Maximum Operating Pressure: 4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Layer Composition And Location:	
4000.0 pounds per square inch single response Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	1st layer braided fiber	
Thread Size: 0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Maximum Operating Pressure:	
0.688 inches all ends Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	4000.0 pounds per square inch single response	
Hydrostatic Test Pressure: 8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Thread Size:	
8000.0 pounds per square inch single response Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	0.688 inches all ends	
Inside Surface Condition: Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Hydrostatic Test Pressure:	
Smooth Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	8000.0 pounds per square inch single response	
Measuring Method And Length: 13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Inside Surface Condition:	
13.500 inches working Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Smooth	
Outside Diameter Tube Accommodated: 0.375 inches all ends Product Name:	Measuring Method And Length:	
0.375 inches all ends Product Name:	13.500 inches working	
Product Name:	Outside Diameter Tube Accommodated:	
	0.375 inches all ends	
Flex hose assembly, acl-fh-83	Product Name:	
	Flex hose assembly, acl-fh-83	



Special Features:

Inner tube nylon with internal support, iaw sae 100r8; inconnel nuts have lockwire holes; mates to cpv 849t-6

Material:

Plastic polyamide tube

Media For Which Designed:

Refrigerant 12 single response

Thread Series Designator:

Un all ends

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0