

View Online at <https://aerobasegroup.com/nsn/4720-01-557-7913>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand all ends

Inside Diameter:

0.480 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response

Outside Diameter:

0.700 inches

Minimum Inside Bending Radius:

1.000 inches

Inner Conveying Tube Style:

Plain

End Application:

Obtt controller

Connection Style:

Swivel nut flare all ends

End Connection Design:

Straight all ends

Connection Type:

Threaded internal tube all ends

Thready Qty Per Inch (tpi):

18 1st end

Burst Test Pressure:

500.0 pounds per square inch single response

Layer Composition And Location:

1st layer molded rubber, synthetic

Maximum Operating Pressure:

125.0 pounds per square inch single response

Thread Size:

0.750 inches 2nd end

Seat Angle:

37.0 degrees all ends

Hydrostatic Test Pressure:

250.0 pounds per square inch single response

Inside Surface Condition:

Smooth

Measuring Method And Length:

45.000 inches working

Outside Diameter Tube Accommodated:

0.500 inches 2nd end

Product Name:

Hose eafw

Special Features:

Export control; outer cover and fittings are 300 series stainless steel, passivated; inner liner pfa, aramid fiber reinforcement cres wire braid

Material:

Steel

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unj all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0