

View Online at <https://aerobasegroup.com/nsn/4720-01-559-3074>

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Minimum Inside Bending Radius:**

2.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

45.0

**End Application:**

Ac-130u

**End Connection Design:**

Straight 1st end

**Min. Tensile Strength (psi):**

3000 pounds per square inch

**Burst Test Pressure:**

6500.0 pounds per square inch 2nd response

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Abrasion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

129.000 inches working

**Special Features:**

Burst pressure 1000psi measured at room temp, 6500 psi measured at high temp, end fittings are class 2 made from combination aluminum and corrosion resistant steel (cres)

**Material:**

Stainless steel outside

**Media For Which Designed:**

Oil, lubricating, diester base 4th response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0