

View Online at <https://aerobasegroup.com/nsn/4720-01-559-8155>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand all ends

Inside Diameter:

Between 1.125 inches and 1.175 inches

Temperature Rating:

-55.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response

Outside Diameter:

Between 1.456 inches and 1.518 inches

Minimum Inside Bending Radius:

4.500 inches

Inner Conveying Tube Style:

Plain

Exterior Color:

Green, olive

End Application:

2340-01-447-3889

Connection Style:

Swivel nut flare all ends

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube all ends

Thready Qty Per Inch (tpi):

12.0 all ends

Burst Test Pressure:

1250.0 pounds per square inch single response

Layer Composition And Location:

1st layer braided fabric or 2nd layer braided steel wire or outer layer rubber impregnated braided fabric

Maximum Operating Pressure:

300.0 pounds per square inch 1st response

Thread Size:

1.312 inches all ends

Seat Angle:

37.0 degrees all ends

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

2031.5 millimeters working

Seat Radius:

37.000 inches all ends

Outside Diameter Tube Accommodated:

1.000 inches all ends

Material:

Steel

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Un all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0