NSN 4720-01-560-1015

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-560-1015

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b all ends |
| Thread Direction: |
| Right-hand all ends |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -70.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.510 inches |
| Minimum Inside Bending Radius: |
| 1.750 inches |
| End Application: |
| Vdsdr assembly |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube all ends |
| Thready Qty Per Inch (tpi): |
| 18 all ends |
| Burst Test Pressure: |
| 12000.0 pounds per square inch single response |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.562 inches all ends |
| Flow Angle: |
| 45.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 45.000 inches working |
| Outside Diameter Tube Accommodated: |
| 0.250 inches all ends |
| Material: |
| Stainless steel |
| Thread Series Designator: |
| Unf all ends |
| Shelf Life: |
| N/a |

NSN 4720-01-560-1015

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0