---

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-560-1117

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b all ends   |
| Thread Direction:   |
| Right-hand all ends   |
| Inside Diameter:  |
| 0.375 inches  |
| Tempurature Rating:   |
| -70.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.720 inches  |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| End Application:  |
| Vdsdr assembly  |
| End Connection Design:  |
| Straight all ends   |
| Connection Type:  |
| Threaded internal tube all ends   |
| Thready Qty Per Inch (tpi):   |
| 18 2nd end  |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch single response  |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch single response   |
| Thread Size:  |
| 0.687 inches 1st end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 52.000 inches working   |
| Outside Diameter Tube Accommodated:   |
| 0.375 inches all ends   |
| Material:   |
| Stainless steel   |
| Thread Series Designator:   |
| Unf 2nd end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |



Demilitarization:

Yes - demil/mli

Fiig:

A542a0