NSN 4720-01-568-2696

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-568-2696

Cross Sectional Shape:
Round
Thread Direction:
Right-hand all ends
Inside Diameter:
0.250 inches
Outside Diameter:
0.687 inches
Minimum Inside Bending Radius:
4.000 inches
Inner Conveying Tube Style:
Plain
End Application:
End item nsn: 2320-01-522-1859; fmtv, 10 ton w/winch
Connection Style:
Swivel nut flare all ends
End Connection Design:
Straight all ends
Connection Type:
Threaded internal hose all ends
Burst Test Pressure:
20000.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber and 2nd layer braided steel wire and 3rd layer molded rubber, chloroprene
Maximum Operating Pressure:
5000.0 pounds per square inch
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees all ends
Inside Surface Condition:
Smooth
Measuring Method And Length:
53.750 inches and 54.500 inches
Inside Diameter Hose Accommodated:
0.250 inches all ends
Product Name:
Product Name: Hose, hydraulic

Unf all ends

Thread Series Designator:

NSN 4720-01-568-2696

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0