NSN 4720-01-579-9624

Air Duct Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-579-9624

Cross Sectional Shape:
Round
Inside Diameter:
2.000 inches both ends
Tempurature Rating:
-75.0 degrees fahrenheit and 500.0 degrees fahrenheit
Outside Diameter:
2.300 inches both ends
End Application:
Uh-1
Endlength:
1.250 inches both ends
Connection Style:
Round both ends
Connection Type:
Soft both ends
End Inside Diameter:
2.000 inches both ends
Maximum Operating Pressure:
4.0 pounds per square inch
Measuring Method And Length:
Measuring Method And Length: 12.000 inches excluding end fittings
12.000 inches excluding end fittings
12.000 inches excluding end fittings Product Name:
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure:
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features:
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material:
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire Style Designator:
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire Style Designator: Bead reinforced
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire Style Designator: Bead reinforced Shelf Life:
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire Style Designator: Bead reinforced Shelf Life: N/a
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire Style Designator: Bead reinforced Shelf Life: N/a
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire Style Designator: Bead reinforced Shelf Life: N/a Unit Of Measure:
12.000 inches excluding end fittings Product Name: Duct-air, flexible helix wire supported External Operating Pressure: 4.1 pounds per square inch Special Features: Wire helix, spring steel is bronze plated Material: Steel reinforcing wire Style Designator: Bead reinforced Shelf Life: N/a Unit Of Measure: Demilitarization: