Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-580-0647

ſ	cross Sectional Shape:
	cound
	bread Direction:
-	light-hand all ends
	nside Diameter:
-	.750 inches
	empurature Rating:
	100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
-	Outside Diameter:
	.090 inches
	Inimum Inside Bending Radius:
-	.000 inches
	Ind Application:
	1k86 mod o gun mount assembly
	connection Style:
	wivel nut, inverted flare all ends
	connection Type:
	hreaded internal tube all ends
	urst Test Pressure:
	000.0 pounds per square inch
L	ayer Composition And Location:
	st layer polytetrafluoroethylene impregnated glass fiber and outer layer braided steel wire
Ν	laximum Operating Pressure:
1	000.0 pounds per square inch
Т	hread Size:
1	.062 inches all ends
S	eat Angle:
3	7.0 degrees all ends
Ir	nside Surface Condition:
С	Convoluted
M	leasuring Method And Length:
5	3.000 inches
т	hread Series Designator:
Ν	lptf all ends
S	helf Life:
Ν	l/a
U	Init Of Measure:
D	emilitarization:
Ν	lo
F	iig:
А	542a0