## NSN 4720-01-581-6608

Nonmetallic Tubing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-581-6608

| Cross Sectional Shape:  |
|---|
| Round   |
| Inside Diameter:  |
| 0.170 inches  |
| Outside Diameter:   |
| 0.250 inches  |
| Minimum Inside Bending Radius:  |
| 1.000 inches  |
| End Application:  |
| Husky vehicle; air brake system   |
| Burst Test Pressure:  |
| 1200.0 pounds per square inch single response   |
| Product Name:   |
| Nylon 12 tubing   |
| Special Features:   |
| Matl is single wall extrusion of 100% virgin, heat and light stabilized nylon 12 (polyamide); smooth and seamless; core free from         |
| obstructions or foreign matl; temp range: -40.0 to +200.0 degrees f   |
| Material:   |
| Plastic polyamide   |
| Supplementary Features:   |
| Resistant to attack by gasoline, diesel fuel, methyl alcohol, and zinc chloride; not to be used in area subject to attack by battery acid |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A54200  |
|   |
|   |