

View Online at <https://aerobasegroup.com/nsn/4720-01-588-7015>

**Cross Sectional Shape:**

Round

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

**Outside Diameter:**

0.375 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

0.0

**End Application:**

U-2

**Connection Style:**

Swivel nut flare all ends

**End Connection Design:**

Elbow all ends

**End Fitting Component And Material:**

Body stainless steel all ends

**Connection Type:**

Threaded internal tube all ends

**Burst Test Pressure:**

6500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

9.500 inches working

**Product Name:**

Hose assembly, polyterafluorethylene, permanently attached fittings, high temperature, medium pressure, flare-to-flare

**Special Features:**

Also designed for water-alcohol media; reinforced with corrosion resistant steel wire braid

**Media For Which Designed:**

Oil 2nd response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0