

View Online at <https://aerobasegroup.com/nsn/4720-01-588-7015>

Cross Sectional Shape:

Round

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.375 inches

Minimum Inside Bending Radius:

4.000 inches

Angle Between Rigid Elbow Fittings In Deg:

0.0

End Application:

U-2

Connection Style:

Swivel nut flare all ends

End Connection Design:

Elbow all ends

End Fitting Component And Material:

Body stainless steel all ends

Connection Type:

Threaded internal tube all ends

Burst Test Pressure:

6500.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

9.500 inches working

Product Name:

Hose assembly, polyterafluorethylene, permanently attached fittings, high temperature, medium pressure, flare-to-flare

Special Features:

Also designed for water-alcohol media; reinforced with corrosion resistant steel wire braid

Media For Which Designed:

Oil 2nd response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0