## NSN 4720-01-590-5339

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-590-5339

Cross Sectional Shape:
Round
Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Inside Diameter:
0.173 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.410 inches
Minimum Inside Bending Radius:
1.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare all ends
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Body steel comp 303 all ends and body steel comp 304 all ends and body steel comp 316 all ends and body steel comp 321 all ends
Connection Type:
Threaded internal tube all ends
Thready Qty Per Inch (tpi):
20 all ends
Layer Composition And Location:
1st layer molded polytetrafluoroethylene and 2nd layer braided corrosion resistant steel wire and outer layer braided textile yarn
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches all ends
Seat Angle:
37.0 degrees all ends
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:

## NSN 4720-01-590-5339

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	I ength:
Measainig	Mictiloa	Alla	Longin.

17.000 inches working

**Product Name:** 

Medium pressure hydraulic hose, ptfe inner tube reinforced with cres wire draid and protected by black nylon abrasion resistant cover

**Special Markings:** 

Mark shall be in accorance with sae-as478

Media For Which Designed:

Hydraulic fluid 2nd response

**Thread Series Designator:** 

Unjf all ends

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0