NSN 4720-01-590-5340

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-590-5340

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand all ends
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.772 inches
Minimum Inside Bending Radius:
5.500 inches
Exterior Color:
Blue
Angle Between Rigid Elbow Fittings In Deg:
120.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
End Fitting Component And Material:
Body stainless steel all ends
Connection Type:
Threaded internal tube all ends
Thready Qty Per Inch (tpi):
14 2nd end
Layer Composition And Location:
1st layer molded polytetrafluoroethylene and 2nd layer helix steel coil and 2nd layer spiral interlocked corrosion resistant steel and outer
layer braided polyester cord
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
Flow Angle:
120.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant
Inside Surface Condition:
Smooth

Measuring Method And Length: 23.630 inches and 23.870 inches

NSN 4720-01-590-5340

Nonmetallic Hose Assembly - Page 2 of 2



Product Name:

Medium pressure high temperature hydraulic hose, ptfe inner tube reinforced with cres wire braid protected by a blue braided polyester abrasion resistant cover.

Special Features:

Internal support coil made from 302 or 304 cres flat stock with od 0.510 inches

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unjf 1st end

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

No

Fiig:

A542a0