Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-597-6637

| _ | |
|---|---|
| | Cross Sectional Shape: |
| | Round |
| | nside Diameter: |
| | .250 inches |
| | Inimum Inside Bending Radius: |
| | 3.250 inches |
| E | Exterior Color: |
| E | Black |
| E | End Application: |
| 2 | 320-01-543-0651 |
| E | End Fitting Component And Material: |
| h | nsert steel all ends |
| C | Connection Type: |
| Т | hreaded external boss all ends |
| E | Burst Test Pressure: |
| 9 | 000.0 pounds per square inch |
| L | ayer Composition And Location: |
| 1 | st layer molded rubber, nitrile and 2nd layer braided steel wire and outer layer molded rubber, synthetic |
| N | laximum Operating Pressure: |
| 2 | 250.0 pounds per square inch |
| h | nside Surface Condition: |
| S | Smooth |
| N | leasuring Method And Length: |
| 2 | 29.500 inches |
| F | Product Name: |
| F | lose assembly number 20 cr 29.50 2497 |
| S | Shelf Life: |
| Ν | I/a |
| ι | Jnit Of Measure: |
| | - |
| C | Demilitarization: |
| Ν | lo |
| F | iig: |
| A | A542a0 |