NSN 4720-01-598-7181

Nonmetallic Hose - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-598-7181

| Cross Sectional Shape: |
|---|
| Round |
| Wall Thickness: |
| 0.062 inches |
| Inside Diameter: |
| 0.251 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| Between 0.371 inches and 0.379 inches |
| Minimum Inside Bending Radius: |
| 1.5 inches |
| Inner Conveying Tube Style: |
| Plain |
| Exterior Color: |
| Black |
| Burst Test Pressure: |
| 950.0 pounds per square inch single response |
| Layer Composition And Location: |
| 2nd layer braided polyester cord |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch single response |
| Outer Covering Environmental Protection: |
| Heat resistant and light resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 100.0 feet |
| Special Features: |
| Core tubing is heat resistant polyamide, cover tubing is heat & light resistant polyamide |
| Material: |
| Plastic polyamide |
| Media For Which Designed: |
| Air single response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A541z0 |