NSN 4720-01-598-7943

Pipe Size Accommodated:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-598-7943

| 0.500 inches all ends |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Direction: |
| Right-hand all ends |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.800 inches |
| Minimum Inside Bending Radius: |
| 3.5 inches |
| End Application: |
| Mrap; rg-33 |
| Connection Style: |
| Swivel nut, compression all ends |
| Connection Type: |
| Threaded internal boss all ends |
| Burst Test Pressure: |
| 12000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Abrasion resistant |
| Measuring Method And Length: |
| 81.0 inches |
| Inside Diameter Hose Accommodated: |
| 0.500 inches all ends |
| Outside Diameter Tube Accommodated: |
| 0.813 inches all ends |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Thread Series Designator: |
| Nptf all ends |
| Shelf Life: |
| N/a |

NSN 4720-01-598-7943

Nonmetallic Hose Assembly - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A542a0