

View Online at <https://aerobasegroup.com/nsn/4720-01-598-9139>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.485 inches and 0.531 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.937 inches and 0.999 inches

Minimum Inside Bending Radius:

7.0 inches

Inner Conveying Tube Style:

Plain

End Connection Design:

Straight all ends

Connection Type:

Threaded internal hose all ends

Burst Test Pressure:

14000.0 pounds per square inch

Maximum Operating Pressure:

3500.0 pounds per square inch

Outer Covering Environmental Protection:

Ozone resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.500 inches and 18.500 inches

Product Name:

Hose assembly, flexible

Special Features:

Proof test hose to 7000 psi for 30 seconds w/no leaks; reinforcement layer consists of 2 wire braid layers separated by synthetic rubber layer; fittings are female 37 degree flare swivel straight hose - material - stainless steel

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0