Nonmetallic Hose Assembly - Page 1 of 1

AeroBase

View Online at https://aerobasegroup.com/nsn/4720-01-601-5873

Round Sha all mode Say and say all mode	Cross Sectional Shape:
B all ands Function Rating: 2-20 degrees fahrenheit and 13-0.0 degrees fahrenheit single response Exterior Colo: Green Brady that and 13-0.0 degrees fahrenheit single response Brady that and 13-0.0 degrees fahrenheit single response Brady that and 13-0.0 degrees fahrenheit single response Brady that and Brady that and and and Brady that and surface Treatment: Nut anotica all ands Brady Chy Per Inch (tpt): 20 tarded Brady that Per Inch (tpt): 20 tarded Brady Chy Per Inch (tpt): 20 tarded and and Box propering Pressore: 10:0 pounds per square inch Brady Bethat And Length: 10:0 pounds per square inch Box propering Pressore: 10:0 pounds per square inch Box propering Pressore: 10:0 pounds per square inch	Round
Fundature Rating: -2. degrees fahrenheit and 130.0 degrees fahrenheit single response Exterior Color: Green Green Brand Connection Design: Statuminum alloy all ends End Filting Component And Material: Nut atominum alloy all ends Connection Type: Transdo Internal tube all ends Connection Type: Transdo presence: 10.0 pounds per square inch 20.1 strading 10.0 pounds per square inch	Thread Class:
 22.0 degrees fahrenheit and 130.0 degrees fahrenheit single response 22.0 degrees fahrenheit and 130.0 degrees fahrenheit single response 23.0 degrees fahrenheit and 130.0 degrees fahrenheit single response 24.0 degrees fahrenheit and 130.0 degrees fahrenheit single response 24.0 degrees fahrenheit single response 25.0 degr	3b all ends
Exterior Color: Green Extendior Design: Straight Ist end Exterior Tables and Extendior Component And Material: Nut andica all ends Fitting Component And Surface Treatment: Nut andica all ends Connection Type: Threadd internal tube all ends Threadd internal tube all ends Threadd internal tube all ends Straight Ist Set Pressure: 300 op ounds per square inch Maximum Operating Pressure: 1000 op unds per square inch Maximum Operating Pressure: 1000 op unds per square inch Maximum Operating Pressure: 1000 pointids per square inch Maximum Operating Pressure: <t< td=""><td>Tempurature Rating:</td></t<>	Tempurature Rating:
Green	-22.0 degrees fahrenheit and 130.0 degrees fahrenheit single response
Enclonnection Design: Straight 1st end Entring Component And Material: Nut aluminum alloy all ends Entring Component And Surface Treatment: Nut anodize all ends Connection Type: Thread of the main tube all ends Thread yap Per Inch (pt): 20 1st end Bustimum Deperation Pressure: 100.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch Massum Operating Pressure: 100.0 pounds per square inch Massum Operating Pressure: 100.0 pounds per square inch Massum Operating Pressure: 100.0 pounds per square inch Maximum Operating Pressure:	Exterior Color:
Straight 1st and Fitting Component And Material: Nut adminum alloy all ends Fitting Component And Surface Treatment: Nut anodize all ends Connection Type: Threaded internal tube all ends Threaded internal tube all ends Threade graves inch Burst Test Pressure: 3000 pounds per square inch Maximum Operating Pressure: 1000 pounds per square inch Measuring Method And Length: 15250 inches 1st end Measuring Method And Length: 15250 inches Product Name: Hose assembly: fareless pro oxygen hose Special Features: Hose assembly: fareless pro oxygen hose Thread Strais Designation: Interd Strais Designatin: Int of Measure:<	Green
Arring Component And Material: Nut aluminum alloy all ands Fitting Component And Surface Treatment: Nut anodaze all ends Concertion Type: Threaded internal tube all ends Thready City Per Inch (tpi): 2014 control 2015 control 2015 control 2016 control 2017 control 2010 controls per square inch Maximum Operating Pressure: 2020 controls per square inch Maximum Operating P	End Connection Design:
Natalaminum alloy all ends Fitting Component And Surface Treatment: Nationation all ends Connection Type: Threaded internal tube all ends Interaction internal tube all ends Threaded internal tube all ends Differentiation all ends Threade Streement 100 pounds per square inch Maximum Operating Pressure: 100 pounds per square inch Thread Streement 100 pounds per square inch Streement 100 pounds per square inch 100 pounds per square i	Straight 1st end
Fitting Component And Surface Treatment: Nut anodize all ends Foread of the main tube all ends Thread Of Per Inch (tpi): 20 Ist end Burst Test Pressure: 00.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch 100.0 pounds per squar	End Fitting Component And Material:
Nata addize all ands Connection Type: Threaded internal tube all ends Thready Oxy Per Inch (tpi): 20 1st and Bust Cast Pressure: 300.0 pounds per square inch Mainum Oxperating Pressure: 0.500 inches st end Doop on the set st end Stating Method And Length: 15.250 inches and 15.750 inches Product Name: Hose assemble, faterless pvc oxygen hose Special Features: Hose assemble, are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in inmersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is tabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Meta For Which Designet: Oxygen, gaseous single response Traced Series Main Na Int of Measure: Int of Measure: <td>Nut aluminum alloy all ends</td>	Nut aluminum alloy all ends
Connection Type: Threaded internal tube all ends Thready Cyp Per Inch (tpi): 20 1st end Bust Test Pressure: 300.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch Preced Size: 0.500 inches 1st end Product Name: Hoss and 15.750 inches Product Name: Hose assembly, flareless pvc oxygen hose Special Features: Hose assembly, flareless pvc oxygen hose Bust For Which Designed: Oxygen, gaseous single response Hored Series Designator: Inji 1st end Special Features: Init of Measure: Init of Measure: Init of Measure: Init of Measure:	Fitting Component And Surface Treatment:
Invested internal tube all ends Invested Qty Per Inch (tpi): 20 fst end Burst Test Pressure: 300. pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch Thread Size: 0.500 inches 1st end Product Name: Rossemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is a flaidated from clear pue, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304. Polate For Which Designed: Availation: Information: Infor Massure: Information:	Nut anodize all ends
Tready Qty Per Inch (tpl): 20 1st end Burst Test Pressure: 300.0 pounds per square inch Mainum Operating Pressure: 100.0 pounds per square inch Thread Size: 0.500 inches 1st end Mesuring Method And Length: 15.250 inches and 15.750 inches Product Name: Hose assembly: flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated form clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designet: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Mainu Life: Na Unif Of Measure: Image:	Connection Type:
20 1st end Burst Test Pressure: 300.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch Fraced Size: 0.500 inches 1st end Burstring Method And Length: 15.250 inches and 15.750 inches Product Name: Hose assembly: flareless pvc oxygen hose Special Features: Hose assembly: flareless pvc oxygen hose Special Features: Hose assembly: flareless pvc oxygen hose Barrier Conder prof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Hored Series Designator: Unif 1st end Sheft Life: Na Inclinatization: Inclinatization: Inclinatization: No Sheft Life: Na Inclinatization: Inclinatization: Inclinatization: No Sheft Life: Na <	Threaded internal tube all ends
Burst Tesk Pressure: 300.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 15.250 inches and 15.750 inches Product Name: Hose assembly, flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Sheft Life: Na Unit Of Measure: - Demilitarization: No Fig:	Thready Qty Per Inch (tpi):
300.0 pounds per square inch Maximum Operating Pressure: 100.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 15.500 inches and 15.750 inches Product Name: Hose assembly, fitareless pur coxygen hose Special Features: Hose assembly stare identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pur, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Mai Unif Of Measure: - Demilitarization: No No Fig:	20 1st end
 kakinum Operating Pressure: 100.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 15.250 inches and 15.750 inches Product Name: Rose assembly, flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in inpersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Maia For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Sheft Life: Na Into Measure: - Demilitarization: No Fig: 	Burst Test Pressure:
100.0 pounds per square inch Thread Size: 0.500 inches 1st end Measuring Method And Length: 15.250 inches and 15.750 inches Product Name: Hose assembly, flareless pvc oxygen hose Spcial Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in inmersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Sheft Life: N/a Into of Measure: - - Demilitarization: No Into of Measure: - Into of Measure: - Into of Measure: - Into if Measure: - Into if Measure: - Into if Measure: - Intof Measure: -	300.0 pounds per square inch
Thread Size: 0.500 inches 1st end Measuring Method And Length: 15.250 inches and 15.750 inches Product Name: Hose assembly, flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Sheff Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Maximum Operating Pressure:
 b.500 inches 1st end Measuring Method And Length: 15.250 inches and 15.750 inches Product Name: Hose assembly, flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig: 	100.0 pounds per square inch
 Measuring Method And Length: 15.250 inches and 15.750 inches Forduct Name: Hose assembly, flareless pvc oxygen hose Special Features: Hose assemblis are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Sheff Life: N/a Unit Of Measure: - mentilitarization: No Fig: 	Thread Size:
15.250 inches and 15.750 inches Product Name: Hose assembly, flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Sheft Life: Iva Iva Iva Iva Fire Iva	0.500 inches 1st end
 Product Name: Hose assembly, flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unjf 1st end Shelf Life: Na Inf Of Measure: - Demilitarization: No Fig: 	Measuring Method And Length:
 Hose assembly, flareless pvc oxygen hose Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Shelf Life: Na Unit Of Measure: Demilitarization: No Fig: 	
Special Features: Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Product Name:
 Hose assemblies are identical in construction to equivalent types in hydrawflow drawing 38001; hose assembly is to be functionally tested in immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unif 1st end Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig: 	
 immersed water to proof pressure of 200 psig using nitrogen as fluid medium for one minute; maximum weight is 1.06 weight; inner tube is fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: 	-
fabricated from clear pvc, cover is aramid fiber and internal support spring is fabricated with cres, type 302/304 Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Media For Which Designed: Oxygen, gaseous single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Oxygen, gaseous single response Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thread Series Designator: Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
Unjf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	-
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
No Fiig:	Unit Of Measure:
No Fiig:	 Domilitarization
Fiig:	
-	
	-
	A042aU