NSN 4720-01-615-0432

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-615-0432

| Cross Sectional Shape: |
|---|
| Round |
| Tempurature Rating: |
| -50.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Minimum Inside Bending Radius: |
| 5.0 inches |
| End Application: |
| Nsn 2320-01-544-2244 truck, palletized loading |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel all ends |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 650.0 pounds per square inch |
| Maximum Operating Pressure: |
| 162.0 pounds per square inch |
| Thread Size: |
| 2.00 inches 1st end |
| Flow Angle: |
| 65.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 39.5 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |
| |