## NSN 4720-01-624-6053

Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-01-624-6053

Cross Sectional Shape: Round Tempurature Rating: -40.0 degrees fahrenheit and 350.0 degrees fahrenheit single response End Application: Stryker vehicle End Connection Design: Straight 2nd end Connection Type:
Tempurature Rating: -40.0 degrees fahrenheit and 350.0 degrees fahrenheit single response End Application: Stryker vehicle End Connection Design: Straight 2nd end
-40.0 degrees fahrenheit and 350.0 degrees fahrenheit single response  End Application:  Stryker vehicle  End Connection Design:  Straight 2nd end
End Application: Stryker vehicle End Connection Design: Straight 2nd end
Stryker vehicle  End Connection Design:  Straight 2nd end
End Connection Design: Straight 2nd end
Straight 2nd end
Connection Type:
31.
Threaded internal hose all ends
Burst Test Pressure:
12000.0 pounds per square inch
Maximum Operating Pressure:
6000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Measuring Method And Length:
358.4 millimeters working and 364.4 millimeters working
Media For Which Designed:
Hydraulic fluid single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0
A542a0