

View Online at <https://aerobasegroup.com/nsn/4720-01-625-3451>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.312 inches

**Tempurature Rating:**

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit 1st response

**Outside Diameter:**

0.469 inches

**Minimum Inside Bending Radius:**

4.00 inches

**End Application:**

Cable

**Connection Style:**

Flare all ends

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube all ends

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

48.0 inches

**Outside Diameter Tube Accommodated:**

0.375 inches all ends

**Product Name:**

124 ptfе flare hose assembly

**Special Features:**

Tube construction - extruded, conductive aerospace polytetrafluoroethylene; application - high temp aircraft and missile fuel, lube oil, coolant, hydraulic, ballistic and pneumatic systems; conductivity conforms to mil-dtl-25579

**Media For Which Designed:**

Fluid single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0