

View Online at <https://aerobasegroup.com/nsn/4720-01-625-3468>

Cross Sectional Shape:

Round

Inside Diameter:

0.406 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit 1st response

Outside Diameter:

0.585 inches

Minimum Inside Bending Radius:

4.62 inches

End Application:

Cable

Connection Style:

Flare all ends

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube all ends

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Hydrostatic Test Pressure:

3000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

76.0 inches

Outside Diameter Tube Accommodated:

0.500 inches all ends

Product Name:

124 ptfе flare hose assembly

Special Features:

Fittings - non-brazed/welded; tube construction - extruded, conductive aerospace polytetrafluoroethylene; application - high temp aircraft and missile fuel, lube oil, coolant, hydraulic, ballistic and pneumatic systems; conductivity conforms to mil-dtl-25579

Media For Which Designed:

Fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0