## NSN 4720-01-633-2085

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-633-2085

Cross Sectional Shape:
Round
Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Tempurature Rating:
-45.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.75 inches
Inner Conveying Tube Style:
Plain
Connection Style:
Swivel nut with loose or integral clinch sleeve all ends
End Connection Design:
Elbow all ends
Connection Type:
Threaded internal tube all ends
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
16 all ends
Layer Composition And Location:
1st layer rubber composition and 2nd layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion
resistant steel wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.75 inches all ends
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
13.0 inches working
Thread Tolerance Class:
3b internal all ends
Outside Diameter Tube Accommodated:
0.75 inches all ends

Hose assembly, nonmetallic

**Product Name:** 

## NSN 4720-01-633-2085

Nonmetallic Hose Assembly - Page 2 of 2



Special	Features:
---------	-----------

Part number incomplete-it does not specify material of fittings or angle between elbow (in 5 degrees increments)

Media For Which Designed:

Fuel/oil, hydrocarbon single response

**Thread Series Designator:** 

Unf all ends

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A542a0