NSN 4720-01-642-5938

N/a

Metallic And Nonmetallic Hose Assembly Set - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/4720-01-642-5956 |
|--|
| Cross Sectional Shape: |
| Round |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.695 inches |
| Minimum Inside Bending Radius: |
| 2.5 inches |
| Connection Style: |
| Swivel, plain all ends |
| End Connection Design: |
| Straight all ends |
| End Fitting Component And Material: |
| Complete fitting steel all ends |
| Fitting Component And Surface Treatment: |
| Complete fitting zinc all ends |
| Connection Type: |
| Threaded internal hose all ends |
| Thready Qty Per Inch (tpi): |
| 16 all ends |
| Layer Composition And Location: |
| 1st layer molded rubber, synthetic and 2nd layer braided steel wire and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 3250.0 pounds per square inch |
| Thread Size: |
| 0.8125 inches 2nd end |
| Outer Covering Environmental Protection: |
| Abrasion resistant |
| Measuring Method And Length: |
| 80.0 inches excluding end fittings |
| Inside Diameter Hose Accommodated: |
| 0.375 inches all ends |
| Media For Which Designed: |
| Hydraulic fluid single response |
| Surface Treatment Specification: |
| Astm b633 type ii fe/zn8, cr6 free zinc assn standard single treatment response |
| Thread Series Designator: |
| Un all ends |
| Shelf Life: |

NSN 4720-01-642-5938

Metallic And Nonmetallic Hose Assembly Set - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A23800