Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-01-643-1140



| Cross Sectional Shape: |
|--|
| Round |
| Inside Diameter: |
| 0.41 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 212.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.75 inches |
| Minimum Inside Bending Radius: |
| 4.62 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight all ends |
| End Fitting Component And Material: |
| Complete fitting copper alloy all ends |
| Connection Type: |
| Unthreaded external hose 2nd end |
| Thready Qty Per Inch (tpi): |
| 16 1st end |
| Burst Test Pressure: |
| 8000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 2000.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Measuring Method And Length: |
| 248.0 inches |
| Inside Diameter Hose Accommodated: |
| 0.41 inches all ends |
| Special Features: |
| Air not to exceed 250 psi or 160 degree f |
| Media For Which Designed: |
| Hydraulic fluid and gas and fuel and oil and air and water single response |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 4720-01-643-1140

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

