Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-01-652-4006

Cross Sectional Shano
Cross Sectional Shape:
Round
Thread Class:
2b all ends
Thread Direction:
Right-hand all ends
Inside Diameter:
0.313 inches
Outside Diameter:
0.609 inches
Minimum Inside Bending Radius:
1.25 inches
End Application:
2350-01-577-0830
Connection Style:
Swivel nut flare all ends
End Connection Design:
Straight all ends
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting zinc all ends
Connection Type:
Threaded internal tube all ends
Thready Qty Per Inch (tpi):
18 all ends
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided fabric and 2nd layer braided wire
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.5625 inches all ends
Seat Angle:
37.0 degrees all ends
Measuring Method And Length:
37.0 inches working
Media For Which Designed:
Fuel and oil single response
Thread Series Designator:
Unf all ends

NSN 4720-01-652-4006

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

