Tube Fitting Clinch Sleeve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-004-4265

Casehardening Indicator:	
Casehardened	
Overall Length:	
Between 0.363 inches and 0.	.366 inches
Metallic Hardness Rating:	
70.0 rockwell b and 99.5 roc	skwell b
End Application:	
2350-01-031-0586	
Flange Outside Diameter:	
Between 0.367 inches and 0.	.372 inches
Seat Angle In Deg:	
40.0	
Sleeve Outside Diameter:	
Between 0.309 inches and 0.	.312 inches
Hose/tube Outside Diamete	er For Which Designed:
0.250 inches	
Special Features:	
Style of design and dim. Appl	licable to each style are optional for ms51825
Material:	
Steel, qq-s-637 or steel, qq-s	s-631
Material:	
Steel comp 1109 or steel con	np 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118 or steel comp 1119 or steel comp 1132 or
steel comp 1137 or steel com	np 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 or steel comp 1145 or steel comp 1146 or
steel comp 1151 or steel com	np 1211 or steel comp 1212 or steel comp 1213 or steel comp 1215 or steel comp b1111 or steel comp b1112 or
steel comp b1113 or steel co	mp 12l14 or steel, qq-s-631
Surface Treatment:	
Cadmium and chromate	
Style Designator:	
Flareless	
Surface Treatment:	
Cadmium, qq-p-416, type 2,	, class 3
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	
Т385-ј	
Mil-std (military Standard):	
Mil-f-18866 spec.	