

View Online at <https://aerobasegroup.com/nsn/4730-00-008-9838>

Thread Class:

3a 2nd end

Connection Style:

Swaged w/ grooves (tube) 1st end

Connection Type:

Unthreaded internal tube 1st end

Thread Size:

0.375 inches 2nd end

Seat Angle:

37.0 degrees 2nd end

Outside Diameter Tube Accommodated:

0.187 inches all ends

Nominallength:

1.391 inches

Special Features:

The internal surface of the permaswage end, will be polytetrafluoroethylene coated; per deutsch co.Spec no. Dmcps1009, to 0.170 in. Min 0.240 in. Max, into the fitting bore

Material:

Steel comp xm-10 or stainless steel

Material Specification:

Ams 5656 assn standard single material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment:

Passivate outside

Surface Treatment Specification:

Mil-s-5002 military specification 1st treatment response inside and deutsch co.Spec no.Dmcps1009 mfr ref 2nd treatment response inside

Style Designator:

Swaged and threaded external

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-f-14072 spec.