

View Online at <https://aerobasegroup.com/nsn/4730-00-008-9838>

**Thread Class:**

3a 2nd end

**Connection Style:**

Swaged w/ grooves (tube) 1st end

**Connection Type:**

Unthreaded internal tube 1st end

**Thread Size:**

0.375 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Outside Diameter Tube Accommodated:**

0.187 inches all ends

**Nominallength:**

1.391 inches

**Special Features:**

The internal surface of the permaswage end, will be polytetrafluoroethylene coated; per deutsch co.Spec no. Dmcps1009, to 0.170 in. Min 0.240 in. Max, into the fitting bore

**Material:**

Steel comp xm-10 or stainless steel

**Material Specification:**

Ams 5656 assn standard single material response

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment:**

Passivate outside

**Surface Treatment Specification:**

Mil-s-5002 military specification 1st treatment response inside and deutsch co.Spec no.Dmcps1009 mfr ref 2nd treatment response inside

**Style Designator:**

Swaged and threaded external

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-f-14072 spec.