NSN 4730-00-033-4550

Quick Disconnect Coupling Half - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-033-4550 **Thread Class:** 3a all ends **Furnished Items:** Cap and chain and lock spring **Overall Length:** 3.875 inches **Quick Disconnect Method:** Quick lead thread all ends **Quick Disconnect Size:** 1.625 inches all ends **Distance From Mounting Flange To Fluid End:** 2.750 inches **Bolt Hole Quantity: Basic Shape Style:** Round first quick disconnect end **Connection Style:** Flareless all ends Leg Length: 1.281 inches **Connection Type:** Threaded external tube first fluid end connection **Features Provided:** Safety locking feature and self-sealing Thready Qty Per Inch (tpi): 12 first quick disconnect end **Thread Size:** 1.062 inches all ends **Mounting Flange Location:** First leg Seat Angle: 12.0 degrees **Outside Diameter:** 2.500 inches Thickness: 0.046 inches **Bolt Hole Diameter:** 0.188 inches **Bolt Circle Diameter:** 2.130 inches

Outside Diameter Tube Accommodated:

0.750 inches all ends

NSN 4730-00-033-4550

Quick Disconnect Coupling Half - Page 2 of 2



Special Features:
W/bulkhead threads on fluid end connection; furnished w/steel chain and aluminum cap
Material:
Aluminum and aluminum alloy body
Surface Treatment:
Anodize body
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response body
Style Designator:
Male coupling half
Thread Series Designator:
Un all ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard): Mil-a-8625 spec.

A531t0