

View Online at <https://aerobasegroup.com/nsn/4730-00-051-5209>

**Thread Class:**

2a all ends

**Maximum Operating Temp:**

250.0 degrees fahrenheit 2nd response

**End Application:**

02n strategic weapon systems (poseidon and trident)

**Connection Style:**

Flared (tube) 1st end

**Connection Type:**

Threaded external tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:**

0.375 inches 1st end

**Nominallength:**

1.375 inches

**Special Features:**

Grumman a10 aircraft

**Material:**

Steel comp 316 or steel comp 304

**Material Specification:**

66, 300 series federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 1st response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 2 federal specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

1 flared sleeve and 1 preformed packing and 1 short coupling nut

**Specification Data:**

96906-ms51525 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0