NSN 4730-00-051-8568

Tube To Hose Straight Adapter - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4730-00-051-8568 |
|--|
| Thread Class: |
| 2b 1st end |
| Maximum Operating Temp: |
| 200.0 degrees fahrenheit single response |
| End Application: |
| 2320-01-097-0248, 2320-01-097-0249, 2320-01-100-7672, 2320-01-097-0260, 2320-01-195-7641 hemtt family (heavy expanded mobility |
| tactical trucks); 2320-01-304-2277 pls (palletized loading system); mrap buffalo mk2a2 |
| Connection Style: |
| Swivel nut, flare (tube) style 3 optional end 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Maximum Operating Pressure: |
| 2250.0 pounds per square inch single response |
| Thread Size: |
| 0.625 inches 1st end |
| Seat Angle: |
| 45.0 degrees 1st end |
| Criticality Code Justification: |
| Feat |
| Inside Diameter Hose Accommodated: |
| 0.310 inches 2nd end |
| Outside Diameter Hose Accommodated: |
| 0.670 inches 2nd end |
| Outside Diameter Tube Accommodated: |
| 0.375 inches 1st end |
| Nominallength: |
| 2.360 inches |
| Special Features: |
| Weapon system essential |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium or zinc outside |
| Thread Series Designator: |
| Unf 1st end |
| Furnished Items And Quantity: |
| 1 hose coupling nut |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 4730-00-051-8568

Tube To Hose Straight Adapter - Page 2 of 2



Fiig:

A080b0