## NSN 4730-00-053-0416

Tube To Hose Straight Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-053-0416
Thread Class:
3b 1st end
Maximum Operating Temp:
135.0 degrees fahrenheit single response
Connection Style:
Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Maximum Operating Pressure:
1250.0 pounds per square inch single response
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end
Seat Radius:
0.540 inches 1st end
Inside Diameter Hose Accommodated:
0.875 inches 2nd end
Outside Diameter Hose Accommodated:
1.109 inches 2nd end
Outside Diameter Tube Accommodated:
1.000 inches 1st end
Nominallength:
2.420 inches
Material:
Aluminum alloy nipple and stainless steel nipple
Media For Which Designed:
Water-oil-gas single response
Surface Treatment:
Anodize and passivate
Thread Series Designator:
Unj 1st end
Furnished Items And Quantity:
1 ferrule sleeve and 1 hose coupling nut
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

## NSN 4730-00-053-0416

Tube To Hose Straight Adapter - Page 2 of 2



Fiig:

A080b0

Mil-std (military Standard):

Mil-f-27272 spec.