

View Online at <https://aerobasegroup.com/nsn/4730-00-054-7650>

Thread Class:

3b 1st end

Maximum Operating Temp:

447.0 degrees fahrenheit 1st response

Connection Style:

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

Connection Type:

Threaded internal tube 1st end

Maximum Operating Pressure:

1500.0 pounds per square inch single response

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 1st end

Inside Diameter Hose Accommodated:

0.188 inches 2nd end

Outside Diameter Hose Accommodated:

0.312 inches 2nd end

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Nominallength:

1.688 inches

Material:

Stainless steel socket

Material Specification:

66, aisi 321/sae 30321 federal standard 1st material response body or 66, aisi 304/sae 30304 federal standard 2nd material response body

Media For Which Designed:

Fluid 1st response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf 1st end

Furnished Items And Quantity:

1 ferrule sleeve and 1 hose coupling nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A080b0

Mil-std (military Standard):

Mil-f-27272 spec.