

View Online at <https://aerobasegroup.com/nsn/4730-00-056-2268>

Body Style:

Plain

Concentric Hole Depth:

1.980 inches

Concentric Hole Diameter:

0.116 inches

Overall Length:

1.980 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Plain

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Second End Connection Type:

Threaded internal tube

Second End Style Designator:

High pressure flare

Second End Thread Class:

3b

Second End Thread Direction:

Right-hand

Cotter Pin Hole Diameter:

Between 0.159 inches and 0.166 inches

Width Across Flats:

Between 0.741 inches and 0.752 inches

First End Thread Length:

0.780 inches

Second End Thread Length:

0.600 inches

Wrenching Feature Style:

Hexagon

Distance From Bolt End To Hole Center:

1.500 inches

First Diameter From Wrenching Feature:

Between 0.369 inches and 0.375 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.240 inches

First Radial Fluid Hole Diameter:

Between 0.107 inches and 0.112 inches

Distance From First Radial Hole Center To End Of Bolt:

0.190 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

1.020 inches

Wrenching Feature Height:

0.960 inches

Hardness Rating:

Between 26.0 rockwell c and 33.0 rockwell c

First End Thread Series Designator:

Unf

First End Thread Size:

0.375 inches

Second End Thread Size:

0.500 inches

Second End Thread Series Designator:

Unf

Special Features:

Three cotter pin holes thru

Material:

Steel

Material Specification:

Ams6415 assn standard all material responses

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type 1 class 2 federal specification all treatment responses

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0