

View Online at <https://aerobasegroup.com/nsn/4730-00-063-1366>

Body Style:

Relieved

Head Diameter:

1.125 inches

Distance From Centerline To Flat:

0.505 inches

Concentric Hole Diameter:

0.312 inches

Overall Length:

1.060 inches

First End Connection Type:

Threaded external tube

First End Thread Class:

3a

First End Thread Direction:

Right-hand

First End Thread Length:

0.356 inches

Wrenching Feature Style:

Round with wrench flats

First Diameter From Wrenching Feature:

0.662 inches

Second Diameter From Wrenching Feature:

0.550 inches

Third Diameter From Wrenching Feature:

0.674 inches

Fourth Diameter From Wrenching Feature:

0.550 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

0.094 inches

Length From Bearing Surface Of Wrenching Feature To End Of Second Diameter:

0.670 inches

Length From Bearing Surface Of Wrenching Feature To End Of Third Diameter:

0.782 inches

Length From Bearing Surface Of Wrenching Feature To End Of Fourth Diameter:

0.875 inches

First Radial Fluid Hole Diameter:

0.187 inches

Distance From First Radial Hole Center To End Of Bolt:

0.315 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

0.875 inches

Wrenching Feature Height:

0.185 inches

Pressure Rating:

1500.0 pounds per square inch

First End Thready Qty Per Inch (tpi):

16

First End Thread Series Designator:

Unf

First End Thread Size:

0.750 inches

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-268, t4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-a-8625 spec.