

View Online at https://aerobasegroup.com/nsn/4730-00-065-0525

Thread Class:         3a 1st end         Connection Style:         Flared (ube) 1st end         Flareg center bulkhead         Connection Type:         Threaded external tube 1st end         1022 inches 2nd end         Seat Angle:         37.0 degrees 1st end         1.052 inches center bulkhead         Vided Across Flats:         1.375 inches center bulkhead         Vided Diameter Tube Accommodated:         0.750 inches 1st end         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Metrial:         1.843 inches         Metrial:         Stelel         Thread Series Designator:         Unj 1st end         Shelf Life:         Na         Unit Of Measure:         ·         Particut         Fig:	
Connection Style:         Flared (tube) 1st end         Flange Shape:         Hexagon center bulkhead         Connection Type:         Threaded external tube 1st end         Stat Angle:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         Vidt Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Mominallength:         1.843 inches         Hareil:         Steel         Thread Series Designator:         Inj 1st end         Shell         Marei         Unit Of Measure:         -         Temalitarization:	Thread Class:
Flared (tube) 1st end         Flareg Shape:         Hexagon center bulkhead         Connection Type:         Threaded external tube 1st end         Thready Gty Per Inch (tpi):         12 2nd end         Thread Size:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         Vittd Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Mominallength:         1.843 inches         Flated Steis         Steel         Thread Series Designator:         Init of Measure:         Va         Dinit of Measure:         Image:         <	3a 1st end
Flange Shape:         Hexagon center bulkhead         Connection Type:         Threaded external tube 1st end         Thready Qty Per Inch (tpl):         12 2nd end         Thread Size:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         Width Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Mominallength:         1.843 inches         Material:         Steel         Thread Series Designator:         Unj 1st end         Shelf Life:         Na         Pincel Series Designator:         Na         Dist Of Measure:         -         Pincel Series Designator:         Na	Connection Style:
Hexagon center bulkhead         Connection Type:         Ihreaded external tube 1st end         Thready Qty Per Inch (tpi):         12 2nd end         Thread Size:         1.052 Inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 Inches center bulkhead         Width Across Flats:         1.375 Inches center bulkhead         Outside Diameter Tube Accommodated:         0.375 Inches 1st end         Material:         1.843 Inches         Material:         Stel Lite:         Inj st end         Shelf Lite:         Inka         Int Cf Measure:         Init Cf Measure:         Initiatization:         No	Flared (tube) 1st end
Connection Type:         Threaded external tube 1st end         Thready Qty Per Inch (tpi):         12 2nd end         Thread Size:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         Vidth Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.4750 inches 1st end         Mominallength:         1.843 inches         Material:         Steel         Thread Series Designator:         Unj 1st end         Shelf Life:         N/a         Pint Of Measure:         -         Pint Of Measure:         No	Flange Shape:
Threaded external tube 1st end         Inready Qty Per Inch (tpi):         12 2nd end         I 2 2nd end         Inread Size:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         Width Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.375 inches 1st end         Nominallength:         1.843 inches         Material:         Steel         Thread Series Designator:         Unj 1st end         Shelf Life:         N/a         Pint of Measure:         -         To militarization:         No	Hexagon center bulkhead
Tready City Per Inch (tpi):         12 2nd end         Thread Size:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         Width Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Nominallength:         1.843 inches         Material:         Steel         Thread Series Designator:         Unj 1st end         Sheff Life:         N/a         Unit of Measure:         r         Demilitarization:         No	Connection Type:
12 2nd end         Thread Size:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         Width Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Nominallength:         1.843 inches         Material:         Steel         Thread Series Designator:         Unj 1st end         Shelf Life:         N/a         Thread Series Designator:         Int Of Measure:         Image:         Image:      Image:         Imad	Threaded external tube 1st end
Thread Size:         1.062 inches 2nd end         Seat Angle:         37.0 degrees 1st end         Thickness:         0.375 inches center bulkhead         With Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Nominallength:         1.843 inches         Steel         Thread Series Designator:         Unj 1st end         Sheff Life:         Na         Uni Of Measure:         -         Penilitarization:         No	Thready Qty Per Inch (tpi):
1.062 inches 2nd endSeat Angle:37.0 degrees 1st endThickness:0.375 inches center bulkheadWith Across Flats:1.375 inches center bulkheadOutside Diameter Tube Accommodated:0.750 inches 1st endNormallength:1.843 inchesSteelThread Series Designator:Unj 1st endShelf Life:N/aUnit Of Measure:-Demilitarization:No	12 2nd end
Seat Angle:37.0 degrees 1st endThickness:0.750 inches center bulkheadWidth Across Flats:1.375 inches center bulkheadOutside Diameter Tube Accommodated:0.750 inches 1st endNominallength:1.843 inchesMaterial:SteelDiread Series Designator:Unj 1st endSheff Life:N/aDirei Of Measure:Demilitarization:No	Thread Size:
37.0 degrees 1st endThickness:0.375 inches center bulkheadWidth Across Flats:1.375 inches center bulkheadOutside Diameter Tube Accommodated:0.750 inches 1st endNominallength:1.843 inchesMaterial:SteelThread Series Designator:Unj 1st endShelf Life:NaInt of Measure:-Demilitarization:No	1.062 inches 2nd end
Thickness:         0.375 inches center bulkhead         Width Across Flats:         1.375 inches center bulkhead         Outside Diameter Tube Accommodated:         0.750 inches 1st end         Nominallength:         1.843 inches         Material:         Steel         Thread Series Designator:         Unj 1st end         Shelf Life:         N/a         Dnit Of Measure:         -         Demilitarization:         No	Seat Angle:
0.375 inches center bulkhead Width Across Flats: 1.375 inches center bulkhead Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 1.843 inches Material: 1.843 inches Material: Steel Thread Series Designator: Unj 1st end Shelf Life: N/a Unit Of Measure:  Demilitarization: No	37.0 degrees 1st end
Width Across Flats:1.375 inches center bulkheadOutside Diameter Tube Accommodated:0.750 inches 1st end0.750 inches 1st endNominallength:1.843 inchesMaterial:SteelThread Series Designator:Unj 1st endShelf Life:N/aUnit Of Measure:Demilitarization:No	Thickness:
1.375 inches center bulkhead Outside Diameter Tube Accommodated: 0.750 inches 1st end Nominallength: 1.843 inches Material: Steel Thread Series Designator: Unj 1st end Shelf Life: N/a Init Of Measure: - Demilitarization: No	0.375 inches center bulkhead
Outside Diameter Tube Accommodated:0.750 inches 1st endNominallength:1.843 inchesMaterial:SteelThread Series Designator:Unj 1st endShelf Life:N/aUnit Of Measure:Demilitarization:No	Width Across Flats:
0.750 inches 1st end Nominallength: 1.843 inches Material: Steel Thread Series Designator: Unj 1st end Shelf Life: Na Ditt Of Measure:  Penilitarization: No	1.375 inches center bulkhead
Nominallength:1.843 inchesMaterial:SteelThread Series Designator:Unj 1st endShelf Life:N/aUnit Of Measure:Demilitarization:No	Outside Diameter Tube Accommodated:
1.843 inches Material: Steel Thread Series Designator: Unj 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.750 inches 1st end
Material:SteelThread Series Designator:Unj 1st endShelf Life:N/aUnit Of Measure:Demilitarization:No	Nominallength:
Steel Thread Series Designator: Unj 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.843 inches
Thread Series Designator:   Unj 1st end   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No	Material:
Unj 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Steel
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization: No	Unj 1st end
Unit Of Measure:  Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
Νο	Unit Of Measure:
Νο	
	Demilitarization:
Fiig:	No
	Fiig:
A080b0	A080b0