

View Online at <https://aerobasegroup.com/nsn/4730-00-065-3230>

Body Style:

Plain

Concentric Hole Depth:

Between 1.292 inches and 1.302 inches

Concentric Hole Diameter:

Between 0.270 inches and 0.303 inches

Overall Length:

Between 1.823 inches and 1.833 inches

First End Connection Type:

Threaded external tube

First End Style Designator:

Inverted flare

First End Thread Class:

3a

First End Thread Direction:

Right-hand

Width Across Flats:

Between 0.806 inches and 0.812 inches

First End Thread Length:

0.312 inches

Wrenching Feature Style:

Hexagon

First Diameter From Wrenching Feature:

Between 0.558 inches and 0.559 inches

Length From Bearing Surface Of Wrenching Feature To End Of First Diameter:

Between 1.225 inches and 1.239 inches

First Radial Fluid Hole Diameter:

Between 0.249 inches and 0.258 inches

Distance From First Radial Hole Center To End Of Bolt:

Between 1.120 inches and 1.130 inches

Length From Bearing Surface Of Wrenching Feature To Bolt End:

Between 1.604 inches and 1.617 inches

Wrenching Feature Height:

0.229 inches

Min. Tensile Strength (psi):

150000 pounds per square inch

First End Thread Series Designator:

Unf

First End Seat Angle:

45.0 degrees

First End Thread Size:

0.562 inches

Special Features:

Hexagon head phosphate coated

Material:

Steel

Material Specification:

Mil-s-6050, cond f4 military specification single material response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A121a0

Mil-std (military Standard):

Mil-s-6050 spec.