NSN 4730-00-068-0393

Quick Disconnect Reducer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4730-00-068-0393

| The same and the s |
|--|
| Overall Length: |
| Between 7.120 inches and 9.000 inches |
| Quick Disconnect Method: |
| Cam-locking all ends |
| Quick Disconnect Size: |
| 6.000 inches second quick disconnect end |
| Maximum Operating Temp: |
| 75.0 degrees fahrenheit |
| Connection Type: |
| External quick disconnect |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| Special Features: |
| Second end connection type: internal |
| Material: |
| Aluminum alloy body |
| Material Specification: |
| Qq-a-601, federal specification single material response body or qq-a-601, alloy 40e, t5 federal specification single material response body |
| Media For Which Designed: |
| Air |
| Surface Treatment: |
| Anodize body |
| Surface Treatment Specification: |
| Mil-a-8625, type 2, class 1 military specification single treatment response body |
| Furnished Items And Quantity: |
| 1 gasket |
| Specification Data: |
| 96906-ms49000-23 government standard and 81349-mil-c-27487 government specification |
| Specification Or Standard: |
| 4x6 size and 1 style and xi type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A535x0 |

Mil-a-8625 spec.

Mil-std (military Standard):