NSN 4730-00-069-5183



Fluid Pressure Line Multiple Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4730-00-069-5183

Thread Class:
3a second connection

Thread Direction:
Right-hand second connection

Overall Length:
1.718 inches

1.000 inches
Thickness:

Overall Width:

0.500 inches

Thread Size:

7/16 in.-20 second connection

Thread Provision:

Unthreaded first connection

Connection Style:

Socket first connection

Bolt Hole Diameter:

0.563 inches

Seat Angle In Deg:

37.0

Screw Thread Series Designator:

Unf second connection

Seat:

Not included second connection

Fluid Connection Quantity:

2 first connection

Fluid Conveyance Type And Size For Which Designed:

0.563 in. Od tube, 0.563 in. Od tube, 0.250 in. Od tube

Bolt Hole Flats Serrations:

Not provided

Bolt Hole Fluid Passage:

Not provided

Material:

Aluminum alloy, qq-a-268, cond t4

Material:

Aluminum alloy, qq-a-268, cond t4

Surface Treatment:

Anodize

Style Designator:

1 fluid connection

Surface Treatment:

Anodized, mil-a-8625, type 1

NSN 4730-00-069-5183

Fluid Pressure Line Multiple Connector - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:

tion:

No

Fiig:

T385-g