

View Online at <https://aerobasegroup.com/nsn/4730-00-090-0564>

**Thread Class:**

2b 1st end

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

Trident submarine and landing vehicle, tracked (lct-7)

**Connection Style:**

Swivel nut, flare (tube) style 3 optional end 1st end

**Leg Length:**

0.828 inches 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.562 inches all ends

**Seat Angle:**

37.0 degrees 2nd end

**Flow Angle:**

45.0 degrees

**Outside Diameter Tube Accommodated:**

0.375 inches all ends

**Material:**

Stainless steel

**Material Specification:**

66, 300 series federal standard single material response

**Media For Which Designed:**

Hydraulic fluid 2nd response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35, type 1 or 2 federal specification single treatment response

**Thread Series Designator:**

Unf all ends

**Furnished Items And Quantity:**

1 tube coupling nut w/sleeve

**Specification Data:**

96906-ms51522 government standard and 81349-mil-f-18866 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-f-18866 spec.