

View Online at <https://aerobasegroup.com/nsn/4730-00-090-8665>

**Thread Class:**

2a 1st end

**Maximum Operating Temp:**

250.0 degrees fahrenheit single response

**End Application:**

Fuel primer pump assembly model m60a, m60a2 m728, m60a1 tank bridge launcher

**Connection Style:**

Plain (pipe) 2nd end

**Leg Length:**

0.890 inches 1st end

**Connection Type:**

Threaded internal pipe 2nd end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

90.0 degrees

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Material:**

Steel comp 12114

**Material Specification:**

66 federal standard single material response

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment Specification:**

J514 assn standard single treatment response and mil-c-81562, type 1, cl 3 military specification single treatment response and qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf 1st end

**Furnished Items And Quantity:**

1 short coupling nut with sleeve

**Specification Data:**

96906-ms51813 government standard and 81343-j514 professional/industrial association standard

**Specification Or Standard:**

22a figure

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-c-81562 spec.