

View Online at <https://aerobasegroup.com/nsn/4730-00-090-8665>

Thread Class:

2a 1st end

Maximum Operating Temp:

250.0 degrees fahrenheit single response

End Application:

Fuel primer pump assembly model m60a, m60a2 m728, m60a1 tank bridge launcher

Connection Style:

Plain (pipe) 2nd end

Leg Length:

0.890 inches 1st end

Connection Type:

Threaded internal pipe 2nd end

Maximum Operating Pressure:

3000.0 pounds per square inch single response

Thread Size:

0.438 inches 1st end

Seat Angle:

12.0 degrees 1st end

Flow Angle:

90.0 degrees

Outside Diameter Tube Accommodated:

0.250 inches 1st end

Material:

Steel comp 12114

Material Specification:

66 federal standard single material response

Media For Which Designed:

Hydraulic fluid single response

Surface Treatment Specification:

J514 assn standard single treatment response and mil-c-81562, type 1, cl 3 military specification single treatment response and qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unf 1st end

Furnished Items And Quantity:

1 short coupling nut with sleeve

Specification Data:

96906-ms51813 government standard and 81343-j514 professional/industrial association standard

Specification Or Standard:

22a figure

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A080b0

Mil-std (military Standard):

Mil-c-81562 spec.