

View Online at <https://aerobasegroup.com/nsn/4730-00-114-0933>

**Thread Class:**

3b 1st end

**Maximum Operating Temp:**

204.0 degrees fahrenheit 2nd response

**Connection Style:**

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

**Leg Length:**

0.515 inches 1st end

**Connection Type:**

Threaded internal tube 1st end

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

45.0 degrees

**Inside Diameter Hose Accommodated:**

0.217 inches 2nd end

**Outside Diameter Hose Accommodated:**

0.470 inches 2nd end

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Material:**

Stainless steel

**Material Specification:**

Qq-s-763, andclass 304, 304l, 316, 321 and347, cond a federal specification single material response and qq-s-763, class and304, cond b, 7000 psi min ys federal specification 1st material response and qq-w-423, class 304, or 305, cond a federal specification 2nd material response

**Media For Which Designed:**

Hydraulic fluid single response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-dtl 83296 military specification single treatment response

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A080b0

**Mil-std (military Standard):**

spec.