NSN 4730-00-114-2456

Quick Disconnect Coupling Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4730-00-114-2456

Thread Class: 3a first fluid end connection **Overall Length:** 3.543 inches Second Leg Length: 0.548 inches **Quick Disconnect Method:** Spring push-lock all ends **Maximum Operating Temp:** 149.0 degrees celsius single response **End Application:** H-53 helicopter **Connection Style:** Flared first fluid end connection Leg Length: 0.548 inches **Connection Type:** Threaded external tube first fluid end connection Second End Relationship With First End: Identical **Maximum Operating Pressure And Media For Which Designed:** 200.0 pounds per square inch any acceptable **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.562 inches first fluid end connection Seat Angle: 37.0 degrees Maximum Operating Tempurature And Media For Which Designed: 149.0 degrees celsius any acceptable **Outside Diameter Tube Accommodated:** 0.375 inches first fluid end connection **Special Features:** W/provision for locknut Material: Stainless steel **Style Designator:** Coupling assembly **Test Data Document:**

78286-65307-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unf first fluid end connection

NSN 4730-00-114-2456

Quick Disconnect Coupling Assembly - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A531s0