

View Online at <https://aerobasegroup.com/nsn/4730-00-119-9854>

**Thread Class:**

3b 1st end

**Maximum Operating Temp:**

232.0 degrees celsius single response

**Connection Style:**

Swivel nut, flareless (swivel nut attachment method optional) (tube) 1st end

**Leg Length:**

1.875 inches 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Flow Angle:**

90.0 degrees

**Inside Diameter Hose Accommodated:**

0.406 inches 2nd end

**Outside Diameter Hose Accommodated:**

0.562 inches 2nd end

**Outside Diameter Tube Accommodated:**

0.500 inches 1st end

**Material:**

Steel

**Material Specification:**

Qq-s-763, class 304, cond a federal specification single material response and ams5646 assn standard 1st material response and qq-s-763, class 304, cond b federal specification 2nd material response

**Surface Treatment:**

Passivate outside

**Thread Series Designator:**

Unf 1st end

**Furnished Items And Quantity:**

1 flared sleeve and 1 hose coupling nut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A080b0

**Mil-std (military Standard):**

Mil-f-27272 spec.