

View Online at <https://aerobasegroup.com/nsn/4730-00-125-2640>

**Thread Class:**

3b 1st end

**Maximum Operating Temp:**

135.0 degrees celsius single response

**Connection Style:**

Swivel nut, flare (tube) style 3 optional end 1st end

**Connection Type:**

Threaded internal tube 1st end

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

0.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Inside Diameter Hose Accommodated:**

0.500 inches 2nd end

**Outside Diameter Hose Accommodated:**

0.664 inches 2nd end

**Outside Diameter Tube Accommodated:**

0.625 inches 1st end

**Nominallength:**

1.860 inches

**Material:**

Aluminum alloy 6061 nipple

**Surface Treatment:**

Anodize nut

**Surface Treatment Specification:**

Mil-a-8625, type 2, class 2 military specification single treatment response nut

**Thread Series Designator:**

Unjf 1st end

**Furnished Items And Quantity:**

1 hose coupling nut and 1 hose coupling sleeve

**Specification Data:**

96906 - ms27053 government standard and 81349 - mil-dtl-27272 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A080b0

**Mil-std (military Standard):**

Mil-a-8625 spec.